





- exchanger,” *Applied Energy*, Vol. 82, pp. 90-106, (2005).
- [5]. Yasuo Mori and Yutaka Uchida, “Forced convective heat transfer between Horizontal flat plates,” *International Journal of Heat Mass Transfer*, vol. 9, pp. 803-817, (1966).
- [6]. Wen-Jei Yang, “Three kinds of heat transfer augmentation in perforated surfaces,” *Letters in Heat and Mass Transfer*, vol. 5, pp. 1-10, (1978).
- [7]. E. M. Sparrow, V. B. Grannis, “Pressure drop characteristics of heat exchangers consisting of arrays of diamond-shaped pin,” *International Journal of Heat Mass Transfer*, Vol. 34, No. 3, pp. 589-600, (1991).
- [8]. R. F. Babus’Haq, K. Akintunde, and S. D. Probert, “Thermal performance of a pin-fin Assembly,” *International Journal of Heat and Fluid Flow*, Vol. 16, No. 1, pp. 50-55, (1995).
- [9]. [9] Shiki Okamoto, Kazumi Tsunoda, Tomohide Katsumata, Nobuaki Abe, and Masamichi Kijima, “Turbulent near-wakes of periodic array of square blocks on a plate,” *International Journal of Heat and Fluid Flow*, Vol. 17, No. 3, pp. 211-218, (1996).
- [10]. Guo Tingwei, Zhu Tingying, Hu Jichuan and Gong Linghui, “The effect of the geometric parameters of a perforated plate on its heat transfer characteristics,” *Cryogenics*, vol. 36, 443-446, (1996).
- [11]. Tong-Miin Liou, Shih-Hui Chen, “Turbulent heat and fluid flow in a passage disturbed by detached perforated ribs of different heights,” *International Journal of Heat Mass Transfer*, Vol. 41, No. 12, pp. 1795-1806, (1998).
- [12]. E.R. Meinders, K. Hanjalic, “Vortex structure and heat transfer in turbulent flow over a wall-mounted matrix of cubes,” *International Journal of Heat and Fluid Flow*, Vol. 20, pp. 255-265 (1999).
- [13]. Ventsislav Zimparov, “Extended performance evaluation criteria for enhanced heat transfer surfaces: heat transfer through ducts with constant wall temperature,” *International Journal of Heat and Mass Transfer*, Vol. 43, pp. 3133-3155, (2000).
- [14]. M. Tahat, Z. Kodan, B.A. Jarrah, S.D. Probert, “Heat transfers in pin-fin arrays experiencing forced convection,” *Applied Energy*, Vol. 67, pp. 419-442, (2000).
- [15]. Kadir Bilen, Ugur Akyol, Sinan Yapici, “Heat transfer and friction correlations and thermal performance analysis for a finned surface,” *Energy Conversion and Management*, Vol. 42, pp. 1071-1083, (2001).
- [16]. Giovanni Tanda, “Heat transfer and pressure drop in a rectangular channel with diamond-shaped elements,” *International Journal of Heat and Mass Transfer*, Vol. 44, pp. 3529-3541, (2001).
- [17]. Ventsislav Zimparov, “Extended performance evaluation criteria for enhanced heat transfer surfaces: heat transfer through ducts with constant heat flux,” *International Journal of Heat and Mass Transfer*, Vol. 44, pp. 169-180, (2001).
- [18]. M. Yilmaz, O. N. Sara, S. Karsli, “Performance evaluation criteria for heat exchangers based on second law analysis,” *Exergy International Journal*, Vol. 1, No. 4, pp. 278-294, (2001).
- [19]. O. N. Sara, T. Pekdemir, S. Yapici, M. Yilmaz, “Heat-transfer enhancement in a channel flow with perforated rectangular blocks,” *International Journal of Heat and Fluid Flow*, Vol. 22, pp. 509-518, (2001).
- [20]. Jenn-Jiang Hwang, Chau-Chuan Liu, “Measurement of endwall heat transfer and pressure drop in a pin-fin wedge duct,” *International Journal of Heat and Mass Transfer*, Vol. 45, pp. 877-889, (2002).
- [21]. O. N. Sara, “Performance analysis of rectangular ducts with staggered square pin fins,” *Energy Conversion and Management*, Vol. 44, pp. 1787-1803, (2003).
- [22]. T.Y. Yang, “Flow structures and heat transfer characteristics in fan flows with and without blowing vortex generators,” *Experimental Thermal and Fluid Science*, Vol. 28, pp. 273-282, (2004).
- [23]. Ugur Akyol, Kadir Bilen, “Heat transfer and thermal performance analysis of a surface with hollow rectangular fins,” *Applied Thermal Engineering*, Vol. 26, pp. 209-216, (2006).
- [24]. N. Sahiti, A. Lemouedda, D. Stojkovic, F. Durst, E. Franz, “Performance comparison of pin fin in-duct flow arrays with various pin cross-sections,” *Applied Thermal Engineering*, Vol. 26, pp. 1176-1192, (2006).
- [25]. Tzer-Ming Jeng, “Thermal performance of in-line diamond-shaped pin fins in a rectangular duct,” *International Communications in Heat and Mass Transfer*, Vol. 33, pp. 1139-1146, (2006).
- [26]. Kenan Yakut, Nihal Alemdaroglu, Bayram Sahin, Cafer Celik, “Optimum design-parameters of a heat exchanger having hexagonal fins,” *Applied Energy*, Vol. 83, pp. 82-98, (2006).
- [27]. S. Jahangeer, M.K. Ramis, G. Jilani, “Conjugate heat transfer analysis of a heat generating vertical plate,” *International Journal of Heat Mass Transfer*, vol. 50, pp. 85-93. (2007).
- [28]. Bayram Sahin, “A Taguchi approach for determination of optimum design parameters for a heat exchanger having circular-cross sectional pin fins,” *Heat Mass Transfer*, vol. 43, pp. 493-502, (2007).